

Home | Company | Dealers | News | Kino U | Support | Cont

New

LED

FLO Remote

FLO Built-In










Studio Fixtures

Kits

Accessories

Lamps

Rentals

Home > Fixtures Remote > Flathead 80/DMX

Flathead 80/DMX

Intro

Ordering

Kits

Specifications

Photometrics

Videos

- 4Bank/DMX
- Double
- Single
- Mega 4Bank DMX
- Mega Double
- Mega Single
- Flathead 80/DMX
- Mini-Flo

Fixture Specifications

Fixture	Part Number	Lamps	Lamp Type	Dimensions	Weight w/Lamps
Flathead 80	CFX-4808	8	F75 / T12	51 x 24 x 4" (129.5 x 61 x 10cm)	27lb (12kg)

Ballast Specifications

Ballast	Part Number	Input Voltage	Output Frequency	Amperage	Lamp Switching	Output Switching	Dimensions	We
4Bank (x2)	BAL-427-120U	100~240VAC 50/60Hz	25kHz	2 x 2.6A=5.2A	1~4	4ft/2ft	13 x 9.5 x 3" (33 x 24 x 7.6cm)	4.9 (2.
4Bank (x2)	BAL-427-230U	240~100VAC 50/60Hz	25kHz	2 x 1.4A=2.8A	1~4	4ft/2ft	13 x 9.5 x 3" (33 x 24 x 7.6cm)	4.9 (2.
4Bank DMX (x2)	BAL-457-120U	100~240VAC 50/60Hz	25kHz	2 x 2.6A=5.2A	1~4	4ft/2ft	12 x 11 x 3" (30.5 x 28 x 7.6cm)	5.3 (2.
4Bank DMX (x2)	BAL-457-230U	240~100VAC 50/60Hz	25kHz	2 x 1.4A=2.8A	1~4	4ft/2ft	12 x 11 x 3" (30.5 x 28 x 7.6 cm)	5.3 (2.

[Back to the Top](#)

Copyright© 2017 Kino Flo Lighting Systems. All rights reserved.