

Home | Company | Dealers | News | Kino U | Support | Cont.

New

LED

FLO Remote

FLO Built-In










Studio Fixtures

Kits

Accessories

Lamps

Rentals

Home > Fixtures Built-In > Diva-Lite

## Diva-Lite®

Intro

Ordering

Kits

Specifications

Photometrics

Videos

Diva-Lite  
Tegra 4Bank DMX  
BarFly

 [Diva-Lite Spec Sheet download](#)

### Diva-Lite 401 Fixture Specifications

| Fixture            | Input Voltage               | Output Frequency | Amperage | Dimming Range | Lamp Switching | Lamps       | Dimensions   | V L |
|--------------------|-----------------------------|------------------|----------|---------------|----------------|-------------|--|-----|
| Diva-Lite 415 Univ | 100-240VAC<br>50/60Hz, 165W | 80kHz            | 1.4A     | 100~5%        | 4/2            | 4 x 55W CFL | 26 x 12 x 6" w/ 6" barndoors<br>(66x30.5x15cm w/ 15cm doors) | 1 ( |
| Diva-Lite 415 Univ | 240-100VAC<br>50/60Hz, 165W | 80kHz            | 0.7A     | 100~5%        | 4/2            | 4 x 55W CFL | 26 x 12 x 6" w/ 6" barndoors<br>(66x30.5x15cm w/ 15cm doors) | 1 ( |

### Diva-Lite 201 Fixture Specifications

| Fixture       | Input Voltage     | Output Frequency | Amperage | Dimming Range | Lamp Switching | Lamps       | Dimensions   | V L  |
|---------------|-------------------|------------------|----------|---------------|----------------|-------------|--|------|
| Diva-Lite 201 | 120VAC<br>50/60Hz | 30kHz            | 1.1A     | 100~5%        | 2/off          | 2 x 55W CFL | 26 x 7.5 x 6" w/ 3.5" barndoors<br>(66 x 19 x 15cm w/ 9cm doors) | 9 (. |
| Diva-Lite 201 | 230VAC<br>50/60Hz | 30kHz            | 0.6A     | 100~5%        | 2/off          | 2 x 55W CFL | 26 x 7.5 x 6" w/ 3.5" barndoors<br>(66 x 19 x 15cm w/ 9cm doors) | 9 (. |

[Back to the Top](#)

Copyright© 2017 Kino Flo Lighting Systems. All rights reserved.