

M40



Lamphead Type:	Open Face with Facetted Reflector, 4000 W
Reflector Type:	MAX reflector made of high purity aluminium
Lamp Type:	Metal Halide 4000 W/SE; Metal Halide 2500 W/SE
Power Consumption:	4000 W / 2500 W
Voltage Range:	200 V / 115 V
Lamp Base:	G38
Dimmability:	Yes, 50 - 100% via ARRI Ballast Unit
Cable Options:	VEAM, Schaltbau
Correlated Color Temperature:	6000 K
Beam Angle:	18 - 52° (with 4000 W lamp)
Product Weight:	19,0 kg / 41.9 lbs.
Shipping Weight:	34,0 kg / 75 lbs. (incl. pallet)
Product Size (HxWxL):	670 x 402 x 511 mm / 26.4" x 15.8" x 20.1"
Shipping Size (HxWxL):	660 x 595 x 665 mm / 26" x 23.4" x 26.2"
UV Glass Diameter:	300 mm / 11.81"
Accessory Diameter:	400 mm / 15.75" (Scrim)
Barndoor Size:	413 mm / 16.26"
Mounting:	Spigot 28 mm / 1 1/8" (1.1")
Protection Class:	1/IP 23
Certifications:	CE, CB, GS, cNRTL