

OVIDE © SMART ASSIST

SPECIFICATIONS

Specification

Temperature range

Ovide Smart Assist 2 EVO: 32-104°F (0-40°C)

Mass

Ovide Smart Assist 2 EVO: 32,8 Lbs / 14,9 Kg

Dimensions with stand

Ovide Smart Assist 2 EVO: 24×16×6" / 610× 415×150mm (WxHxD)

Dimensions without stand

Ovide Smart Assist 2 EVO: 21.3×12.8×4.7" / 540×326×119mm (WxHxD)

Support

Ovide Smart Assist 2 EVO: Female C-Stand Pin ø1.2×2" / ø30x50mm

Screen size

Ovide Smart Assist 2 EVO: 22"

Touchscreen

Ovide Smart Assist 2 EVO: Yes, capacitive

Screen resolution

Ovide Smart Assist 2 EVO: 4096×2304 pixels

Screen bit depth

Ovide Smart Assist 2 EVO: 10 bit

Screen brightness

Ovide Smart Assist 2 EVO: 500 nits

System hard drive type

Ovide Smart Assist 2 EVO: SSD

Video hard drive type

Ovide Smart Assist 2 EVO: SSD

Inputs

Ovide Smart Assist 2 EVO: 2× SDI

2× XLR-3

1× TC

Genlock

Outputs

Ovide Smart Assist 2 EVO: 6× SDI

1× Composite

1x USB-C

2× USB 3.0

1× USB 2.0

1× TC

1× Gigabit Ethernet

2× XLR-3

Timecode

Ovide Smart Assist 2 EVO: Embedded in SDI (in/out) or LTC BNC

DC Input

Ovide Smart Assist 2 EVO: 18-30vdc

AC Power connection

Ovide Smart Assist 2 EVO: Fischer (Arri type) connector

Camera batteries socket

Ovide Smart Assist 2 EVO: 1× Bebob Cine V-Mount (requires Cine series batteries for full recording capability)

UPS

Ovide Smart Assist 2 EVO: Internal, 2 minutes

Battery hot swap

Ovide Smart Assist 2 EVO: Yes

Power consumption

Ovide Smart Assist 2 EVO: 150w

Control up to

Ovide Smart Assist 2 EVO: 2× HD/2K cameras

Connect up to

Ovide Smart Assist 2 EVO: 16 cameras: 8× Smart Assist
64 cameras: 4× Smart Assist + 4× Quad devices

Wifi

Ovide Smart Assist 2 EVO: SMA connectors

Bluetooth

Ovide Smart Assist 2 EVO: Yes