

RED ONE

CAMERAS REDCAST (/PRODUCTS/4K-BROADCAST) ACCESSORIES (/PRODUCTS/ACCESSORIES)
RED ROCKET (/PRODUCTS/RED-ROCKET) REDCINE-X PRO (/PRODUCTS/REDCINE-X-PRO)



OVERVIEW FEATURES TECH SPECS GALLERY

SENSOR	14 Megapixel MYSTERIUM-X®
PIXEL ARRAY	5120 (h) x 2700 (v)
MAX IMAGE AREA	4480 (h) x 2304 (v)
DYNAMIC RANGE	13+ stops
S/N RATIO	66 dB
LENS COVERAGE	24.2mm (h) x 12.5mm (v) x 27.3 mm (d)
MAX DEPTH OF FIELD	Equivalent to S35mm (Motion) lens Equivalent to 16mm (Motion) lens in 2K RAW
PROJECT TIMEBASE	23.98, 24, 25, 29.97 fps @ 4K and 4.5K resolution 50, 59.94fps @ 2K and 3K resolution
RECORDING FRAME RATES	1–30 fps @ 4.5K, 4K 1–60 fps @ 3K 1–120 fps @ 2K
REDCODE® COMPRESSION	12-bit RAW : RC28, 36, 42 Quality Levels

REDCODE RAW	4.5K (2.4:1)
ACQUISITION FORMATS	4K (16:9, HD, 2:1, and Anamorphic 2:1) 3K (16:9, 2:1, and Anamorphic 2:1) 2K (16:9, 2:1, and Anamorphic 2:1)
DELIVERY FORMATS ¹	4K: DPX, TIFF, OpenEXR (.RED via RREncode Plugin) 2K: DPX, TIFF, OpenEXR (.RED via RREncode Plugin) 1080p RGB or 4:2:2, 720p 4:2:2 : Quicktime, JPEG Avid AAF, MXF. 1080p 4:2:0, 720p 4:2:0 : H.264, .MP4
MONITOR OUTPUTS	HD-SDI and HDMI with Frame Guides and Look Around 720p RGB or 4:2:2 SMPTE Timecode, HANC Metadata, 24-bit 48 kHz Audio
MONITOR OPTIONS	RED LCD 5" Flat Panel Display RED PRO LCD 7" Flat Panel Display BOMB EVF (LCOS) High Definition Viewfinder BOMB EVF (OLED) High Definition Viewfinder
DIGITAL MEDIA	RED CF, REDMAG 1.8"
AUDIO	4 channel, uncompressed, 24-bit 48 kHz
REMOTE CONTROL	USB-2, GPI Trigger
CONSTRUCTION	Aluminum Alloy
WEIGHT	10 lbs (Body only)
OPERATING TEMPERATURE	0°C to 40°C (32°F to 104°F)
STORAGE TEMPERATURE	-20°C to 50°C (-4°F to 122°F)

¹ From REDCINE-X PRO®

LOCATIONS (/LOCATIONS) RED STUDIOS ([HTTP://WWW.REDSTUDIO.COM/HOME](http://www.redstudio.com/home)) CONTACT US ([HTTPS://SUPPORT.RED.COM/ANONYMOUS_REQUESTS/NEW](https://support.red.com/anonymous_requests/new))
PRESS (/PRESS) LEGAL (/LEGAL) HISTORY (/HISTORY) GEAR WE USE (/GEAR-WE-USE) SITEMAP (/SITEMAP)

RED®, RED CAMERA®, RED EPIC®, SCARLET®, RED ONE®, REDRAY™, MYSTERIUM®, MYSTERIUM X®, R3D®, REDCODE®, REDMOTE® and all other trademarks, service marks, trade names logos, and product names of RED used on this site are trademarks or registered trademarks of Red.com, Inc. in the USA and other countries.

Copyright © 2016 RED.COM, INC. All rights reserved.

[SIGN UP FOR UPDATES FROM RED \(/NEWSLETTER\)](#)