

## ARRILUX 21/50 "MINISUN" Description

### ARRILUX 21/50 "MINISUN"

#### ARRILUX 21/50 "MINISUN"

The new ARRI 21/50 MINISUN is the smallest dual wattage daylight lamphead that ARRI has developed to date. Developed with flexibility and versatility in mind, the MINISUN offers multiple features allowing the operator to benefit from its use with many applications. Both the 21W and the 50W discharge lamps can be operated from any DC power source from 12- 30V (e. g. battery belt, car lighter/battery). The bayonet lock offers fast and easy lamp exchange. The faceted cold glass reflector guarantees optimum light output. When the smallest possible light source is needed, the lamphead can be separated from the ballast via a 10m cable with integral igniter. To fit into tight spaces, the connecting cable can be attached to the lamphead either from the rear or from the side. The extrusion technology utilized in this lamphead offers universal mounting versatility.



## ARRILUX 21/50 "MINISUN" Technical Data

### ARRILUX 21/50 "MINISUN"

Measurement: ▶ Metric (m/lx) ▶ US Units (ft/ftc)

Type of Lamphead:	_____	Par
Power:	_____	50 W
Lamp Type:	_____	HID 21 W Reflektor
Supply Voltage:	_____	0 V
Correlated Color Temperature:	_____	6000 K
Lamp Base:	_____	G16
Lens Diameter:	_____	50 mm
Barn Door Size:	_____	64 mm
Filter Insertion Size:	_____	mm
Mounting:	_____	Spigot 16mm
Packed Size:	_____	420 mm - 335 mm - 216 mm
Packed Volume:	_____	30390 ccm
Shipping Weight:	_____	0 kg
Protection Class:	_____	IP 22
Compliance:	_____	CE

**Description:**

---

-  Electronic Battery Ballast / Ignitor 21/50 W
-  4-Leaf Barndoor
-  Narrow Flood Lens 12°
-  Flood Lens 20°
-  Super Flood Lens 50°
-  Super Flood Lens, Frosted Fresnel
-  3/4 CTO (5600-3200K) 50 mm
-  1/2 CTO (5600-3800K) 50 mm
-  1/4 CTO (5600-4500K) 50 mm
-  1/8 CTO (5600-4900K) 50 mm
-  Cable 3,5 m (11 ft) for external ignitor
-  Metal Halogen Lamp 21 W
-  Metal Halogen Lamp 50 W
-  Extension Cable XLR 7m
-  Car Battery Cable Set (Croc Clip Type)
-  Car Battery Cable Set (Terminal Type)
-  Stand AS-01