

S4 / Primes

	18mm	25mm	32mm	40mm	50mm	75mm
T-Stop Range	T2-T22	T2-T22	T2-T22	T2-T22	T2-T22	T2-T22
Angular Rotation of Iris Scale	96°	96°	96°	94°	93°	92°
Min. Marked Object Distance	250 mm 9 in	250 mm 9 in	325 mm 12 in	450 mm 16 in	550 mm 20 in	800 mm 30 in
Close Focus from Lens Front	60 mm 2.5 in	60 mm 2.5 in	119 mm 4.9 in	207 mm 8.4 in	323 mm 13 in	573 mm 23 in
Angular Rotation to MOD Endstop	300°	300°	300°	300°	300°	300°
Max. Diagonal Angle of View for Super 35 Format	80°	62°	50°	41°	34°	22°
Length from Front of Lens to Lens Mount	113 mm 4.5 in	113 mm 4.5 in	129 mm 5 in	141 mm 5.5 in	125 mm 4.9 in	125 mm 4.9 in
Max Front Diameter	110 mm	110 mm	110 mm	110 mm	110 mm	110 mm
Total Weight	1.75 kg 3.85 lbs	1.6 kg 3.5 lbs	1.85 kg 4.0 lbs	2 kg 4.4 lbs	1.5 kg 3.3 lbs	1.75 kg 3.85 lbs

Maximum Format Cover	30mm diameter (Super 35mm format)
Focus Scales	Two opposing focus scales - metric or footage. Scales marked from infinity to MOD.
Focus Drive Gear	140 teeth 0.8 metric module x 6.0mm wide x 98mm from image plane. 140 teeth 0.8 module x 6.0mm wide x 99mm from image plane (300mm)
Iris Scales	Two opposing linear T-scales - whole and third stops marked.
Iris Drive Gear	134 teeth 0.8 metric module x 4.0mm wide 79.5mm from image plane.
Internal Front Fitting Filter	Internal thread for filter adapter M105 x 0.75 pitch (12mm and 14mm not applicable). M120 x 1.0 pitch (150mm). M131 x 1.0 pitch (180mm, 300mm)